

Cart comprising a frame consisting of rear wheel supports, front wheel supports, and handle supports. The front wheel supports and handle supports are connected by hinged folding joints that allow the frame's position to be adjusted and locked in either a folded or unfolded position. Adapters are mounted on the frame, designed to accommodate the installation of attachment devices. The cart includes three pairs of adapters, where the first pair of adapters is the upper pair (8), the second pair is the middle pair (9), and the third pair is the lower pair (10), wherein at least one pair of the upper (8) and middle (9) adapters is located on the handle supports (4), and at least one pair of the upper (8) and middle (9) adapters is removable, and the pair of lower (10) adapters is located on the inner side of the front wheel supports (3) in close proximity to the front wheels and is designed to be non-removable, wherein each lower (10) adapter includes a swivel mechanism (11) designed to allow for changing the position of the lower (10) adapters, wherein, in the operating position, the lower adapters (10) are oriented upward relative to the front wheel supports (3), and the three pairs of adapters (8, 9, 10) provide the following six configurations of operating positions for the adapters (8, 9, 10):

- (i) the upper pair of adapters (8), the middle pair of adapters (9), and the lower pair of adapters (10) in a position opposite to the operating position,
- (ii) the middle pair of adapters (9) and the lower pair of adapters (10) in the operating position,
- (iii) the upper pair of adapters (8) and the lower pair of adapters (10) in the operating position,
- (iv) the middle pair of adapters (9) and the lower pair of adapters (10) in a position opposite to the operating position,
- (v) the middle pair of adapters (9) and the lower pair of adapters (10) in a position other than the operating position, or in a position opposite to the operating position,
- (vi) the upper pair of adapters (8), the middle pair of adapters (9), and the lower pair of adapters (10) in the operating position.